

KENWOOD

TK-7180(H)/8180(H)

VHF/UHF FM Mobile Radios

FleetSync®

GENERAL FEATURES

- 30/50 W (136-174 MHz)
- 30/45 W (450-520, 400-470 MHz)
- Conventional & LTR® Zones
- MPT1327 Trunking Option
- Remote Control Head Option¹
- 12 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function / Status LCD Icons
- RSSI Indicator
- Date & 12/24 Hour Time Clock
- Transmit / Busy / Call Alert / Warn LED
- 6 Backlit PF Keys
- Emergency / AUX Key
- Enhanced Kenwood Audio
- Front Panel Speaker
- Companded Audio
- Voice Inversion Scrambler Built-in
- Easy Option Port
- Encryption / ANI Board Control
- VGS-1 Voice Guide / Storage Option
- Emergency Call Features
- DTMF Encode / Decode²
- Special Alert Tone Patterns³
- Call Key⁴
- Time Out Timer
- Busy Channel Lockout
- Timed Power Off

- DB-25 Accessory Connector⁵
- 9 Programmable AUX I/Os⁵
- 2 Programmable AUX Outputs⁵
- Ignition Sense⁶
- Public Address / Horn Alert Option⁷
- MIL-Spec Standard Mic
- MIL-Spec 12-Key DTMF Mic Option
- Windows® Programming & Tuning⁸
- Windows® Firmware Uploading⁸
- Front Panel Test / Tune
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"⁹
- IP-54/55 Water & Dust Intrusion⁹

CONVENTIONAL ZONES

- 512 Channels / 128 Zones¹⁰
- QT / DQT
- Two-Tone Decode¹¹
- Single / Two-Tone Encode¹¹
- Operator Selectable Tone¹¹
- Dual Priority Scan
- Single & Multi-Zone Scan
- List Scan

TRUNKED ZONES

- 512 GID / 128 Zones¹⁰
- Kenwood LTR® Features¹²

FleetSync®

- FleetSync® or FleetSync® II¹³
- PTT ID Digital ANI
- Selective Call & Group Call
- Status Messaging
- Emergency Status
- Caller ID Display
- Short & Long Text Messages¹⁴
- Power On/Off Status Messages
- Input / Output Status Messages
- FleetSync® GPS Ready¹⁵
- Send GPS PF Key¹⁵
- PTT ID & Emergency GPS Reporting¹⁵
- Status Message Block GPS Reporting¹⁵
- Ignition On/Off GPS Reporting¹⁵
- VGS-1 GPS Data Storage¹⁵,¹⁶
- PC Serial Interface

MDC-1200¹⁷

- PTT ID Digital ANI
- Caller ID Display
- Emergency Status
- Radio Check
- Radio Inhibit



Options

<ul style="list-style-type: none"> KMC-35 Microphone (supplied microphone) KMC-36 Keypad Microphone KMC-9C Control Station Desktop Microphone KRK-10 Control Head Remote Kit (23ft/7m) KCT-46 Ignition Sense Cable 	<ul style="list-style-type: none"> KCT-40 Radio Interface Cable (for KDS-100, KGP-2A/2B) KCT-23M DC Cable (Dash mount / 10 feet) KCT-23M3 DC Cable (Remote mount / 23 feet) KAP-2 Horn Alert/Public Address Relay Unit VGS-1 Voice Guide & Storage Unit 	<ul style="list-style-type: none"> KES-3 External Speaker KES-5 External Speaker (requires KAP-2) KMB-10 Key Lock Adapter KLF-2 Line Noise Filter KPS-10A DC Power Supply 	<ul style="list-style-type: none"> KPS-15 DC Power Supply KDS-100 Mobile Data Terminal KGP-2A/2B GPS Receiver / Modem Unit (requires KCT-39 option)
--	---	---	---

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-7180	TK-7180H	TK-8180	TK-8180H
GENERAL				
Frequency Range				
Type 1	136-174 MHz		450-520 MHz	450-512 MHz
Type 2	-		400-470 MHz	
Number of Channels*				
Zone		Max.128 per Radio		
Ch/GID		Max.250 per Zones		
		(Max.512 [Conv.Ch's +GID's] total per Radio)		
Channel Spacing				
Wide	25 kHz, 30 kHz		25 kHz	
Narrow	12.5 kHz, 15 kHz		12.5 kHz	
Operating Voltage		13.6 V DC±15 %		
Current Drain				
Standby	0.4 A	0.4 A	0.4 A	0.4 A
Receive	1.0 A	1.0 A	1.0 A	1.0 A
Transmit	9.0 A	13.0 A	9.0 A	13.0 A
Duty Cycle		Transmit: 20 %		
Operating Temperature Range		-22 °F ~ +140 °F (-30 °C ~ +60 °C)		
Frequency Stability		±0.00025 % (-22 °F ~ +140 °F)		
Antenna Impedance		50 Ω		
Channel Frequency Spread				
Type 1	38 MHz		70 MHz	
Type 2	-		70 MHz	
Dimensions (W x H x D), Projections not included		6-5/16" x 1-3/4" x 6-3/16" (160 mm x 45 mm x 157 mm)		
Weight (net)		3.3 lbs. (1.5 kg)		
FCC ID				
Type 1	K4437303110	K4437303210	K4437313110	K4437313210
Type 2	-	-	K4437313120	K4437313220
IC Certification				
Type 1	282F-37303110	-	-	-
Type 2	-	-	282F-37313120	-

*Maximum capability depends on the number of programmed Zone and repeater channels.

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V

International Protection Standard

Dust & Water Protection	P54: Radio itself P54/55: Remote Head with KRK-10
------------------------------------	--

*To meet above Mil810 and IP grade, weather proof microphone KMC-35 or KMC-36 has to be connected.

Model	TK-7180	TK-7180H	TK-8180	TK-8180H
RECEIVER (Measurements made per EIA/TIA-603)				
Sensitivity (12dB SINAD)				
Wide		0.25 µV		
Narrow		0.28 µV		
Selectivity**				
Wide	80 dB		80 dB	
Narrow	70 dB		67 dB	
Intermodulation Distortion				
Wide/Narrow		75 dB (±50, 100 kHz)		
Spurious Response**	90 dB		85 dB	
Audio Output (4 Ω Impedance)	4 W with less than 5 % distortion			
TRANSMITTER (Measurements made per EIA/TIA-603)				
RF Output Power				
Type 1	30 to 1 W	50 to 10 W	30 to 1 W	45 to 10 W
Type 2	-	-	(490-520 MHz:25 to 1 W) (490-512 MHz:40 to 10 W)	30 to 1 W 45 to 10 W
Spurious Response		70 dB		
Type of Emission				
Wide		16K0F3E		
Narrow		11K0F3E		
FM Hum & Noise				
Wide		50 dB		
Narrow		45 dB		
Microphone Impedance	600 Ω			
Audio Distortion				
Wide/Narrow	3 %			

** Typical specifications
Specifications are subject to change without notice, due to advancements in technology. FleetSync™ is a registered trademark of JVC KENWOOD Corporation in the United States and/or other countries. LTR™ is a registered trademark of Transcript International. All other trademarks are property of their respective owners.

footnotes from Front:

- 1 KRK-10 remote control kit required.
- 2 DTMF includes PTT ID, Emergency ANI, Manual Encode (KMC-36), Auto-Dial (9 numbers) & Stun.
- 3 Special Alert Tone Patterns operate for 2-Tone, DTMF, FleetSync™ selective call decode.
- 4 Call Key: 6 keys max.; operates for 2-Tone, DTMF and FleetSync status encode.
- 5 DB-25 ACC supports 15 Remote Zone/CH/GID selections, KGP-2A/B (KCT-40 required), KDS-100 (KCT-40 required), data modem, MDT, interconnect.
- 6 KCT-46 ignition sense cable option required; plugs into mobile ignition sense pig-tail cable.
- 7 KAP-2 required: Horn Alert operates for FleetSync™, 2-Tone or DTMF selective call decode.
- 8 KPG-89D required: Windows®98/ NT/ 2000/ Me/XP compatible; English/Spanish screen languages.
- 9 MIL-STD "Driven-Rain" and IP-55 Water/Dust Intrusion apply to remote control head only; IP54 applies to radio chassis.
- 10 Conventional Zones: 512 Channels /128 Zones max. per radio; 250 CH max. per Zone Trunked Zones: 512 GID / 128 Zones max. per radio; 250 GID max. per Zone.
- 11 Two-Tone Decode (4 sets x 4 pairs each); Single / Two-Tone Encode (32 tones), Operator Selectable Tone (40 QT.DQT code pairs).
- 12 Kenwood LTR™ Features include: GID Delete/Add, LTR™ Talk Around /Scan Revert Group Display, System Scan, Group Scan, Auto Search.
- 13 FleetSync™ & FleetSync™ II are not compatible.
- 14 Short Text Messages are radio stored & LCD displayed; Long Text Messages require a KDS-100 and KCT-40.
- 15 FleetSync™ GPS features require an internal GPS board or externally wired GPS receiver with NMEA TTL level serial data output to the internal COM 1 or 2 set to "GPS".
- 16 Requires a VGS-1 option.
- 17 Either MDC-1200 or FleetSync™ can be activated per radio.

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.ca


www.kenwoodusa.com



ISO9001 Registered
Communications Equipment Division
Professional Systems Business Group
JVC KENWOOD Corporation
AQS#30212 Printed in USA